

Document type	Technical Data Sheet
<b>Name</b>	<b>DEKO PRIMER</b>
<b>Description</b>	X-fine grit quartz primer, ideal base for: GRASSELLO, MARMORINO FINE, LIME PAINT, TERRA D'ARTE, OSSIDATO, OXIDE METAL and LIBERTY ARENA. The Dark version of this primer is to be used as base for OSSIDATO DARK and OXIDE METAL IRON.
<b>Composition</b>	Special acrylic polymers, very fine quartz sand, additives, and water
<b>Versions</b>	DEKO PRIMER, DEKO PRIMER DARK
<b>Appearance</b>	Liquid
<b>Colour</b>	Standard version: transparent. Dark version: dark grey
<b>Packaging</b>	2 L and 10 L polyethylene packaging
<b>Application</b>	By hand, using a roller
<b>Type of Surface</b>	Architectural vertical surfaces, interior and exterior.
<b>Dilution</b>	Ready to use, but accepts dilution up to 15% with water
<b>Consumption</b>	100 - 110 ml / sqm
<b>Drying</b>	2 hours at 20°C (60°F) to the touch 24 hours at 20°C (60°F) below the surface
<b>Application temperatures</b>	min 8 max 35°C – R.U. < 85% ca
<b>VOC Classification</b>	EU Directive 2004/42/CE: EU limit value for this product (cat A/I): 200 g/l (2010). This product contains less than 200 g/l of VOC.
<b>Shelf life</b>	24 months when stored according to the recommended guidelines
<b>Storage</b>	In original sealed packaging between 5° and 35°C in a dry, dark environment
<b>Safety Norms</b>	This product may cause skin allergic reactions. It is important to adhere to the prevailing safety and hygiene standards while using it. Refrain from disposing of the product in drains, water bodies, or on the ground. Always keep the product out of reach of children. In the event of ingestion, or allergic reaction seek medical assistance without delay and present the container or label. For further details, consult the safety data sheet.
<b>Disposal</b>	Product must be disposed of according to norms and regulations in force. Containers must be sent for recycling. Follow directions on the packaging.
<b>Application Instructions</b>	<p><b>WARNINGS</b></p> <p>To ensure proper usage, dilution, and application of the products mentioned in these pages, please consult the corresponding technical data sheets.</p> <p>During application and for the following 24 hours, protect the surfaces from sudden temperature change, direct sun light and water. Don't apply in temperatures below 8°C or above 35°. During application make sure that the work area isn't too damp to avoid problems with application times.</p> <p><b>APPLICATION</b></p>

DEKO PRIMER is the ideal base for: GRASSELLO, MARMORINO FINE, LIME PAINT, TERRA D'ARTE, OSSIDATO, OXIDE METAL and LIBERTY ARENA.

DEKO PRIMER DARK is to be used as base for OSSIDATO DARK and OXIDE METAL IRON.

It can be applied on new surfaces of plaster, gypsum and plaster board. It can be applied on old surfaces of plaster and washable paint.

If the product has been diluted, mix often to avoid the sedimentation of the quartz sand

#### **Tools**

Roller. Clean tools with water after use.

We have drawn up the material presented above to the best of our technical and experiential knowledge. Nevertheless, our suggestions and recommendations are not guaranteed. All responsibility for the obtained results lies solely with the method and conditions adopted for the application of the product. Such indications constitute valid support for verifying the product's suitability for the specific case. We reserve the right to make modifications to the present information without previous warning.