

Document type	Technical Data Sheet
Name	PERLA WAX
Description	PERLA WAX is a water-based, semi-transparent decorative and protective treatment designed for mineral, smooth finishes. This metallic wax enhances the surfaces' resistance to liquids, making cleaning easier, and adds a decorative effect with its pearlescent-metallic reflections.
Composition	Paraffins, water, mica powders.
Versions	COPPER, GOLD, SILVER
Appearance	Thick cream
Colour	Depends on the version.
Packaging	1 L polyethylene packaging
Application	By hand, using a soft cloth
Where to use it	Lime and mineral-based plaster finishes such as GRASSELLO, MARMORINO FINE, MEDIUM, COARSE, METALLIC, and similar, smooth finishes. It can be used on both interior and exterior finishes.
Dilution	Ready to use
Consumption	20-30 g/sqm
Drying	2-3 hours at 20°C to the touch, 10 hours in depth
Application temperatures	min 8 max 35°C – R.U. < 85% ca
VOC Classification	EU Directive 2004/42/CE: EU limit value for this product (cat A/I): 200 g/I (2010). This product contains less than 200 g/I of VOC.
Shelf life	24 months when stored according to the recommended guidelines
Storage	In original sealed packaging between 5° and 35°C in a dry, dark environment
Safety Norms	It is important to adhere to the prevailing safety and hygiene standards while using it. Always keep the product out of reach of children. In the event of ingestion, or allergic reaction seek medical assistance without delay and present the container or label.
Disposal	Product must be disposed of according to norms and regulations in force. Containers must be sent for recycling. Follow directions on the packaging.
Application Instructions	Apply PERLA WAX with a soft cloth in minimum thickness. Allow at least one hour of drying time before proceeding with polishing. Polishing can be done manually using our NON-WOVEN FABRIC or with electrical equipment. It's important to avoid leaving excess wax or deposits on the surface. It's crucial to apply all waxes, including PERLA WAX, in a thin layer as their purpose is to seal the porosity of the underlying material. In the case of absorbing finishes, such as MARMORINO Venetian Plaster, we recommend applying a first layer of BEESWAX followed by a very thin layer of PERLA WAX. Please note that excessive wax left on the finish may result in stains, as the greasy components of the wax can be absorbed by the surface. The initial layer of BEESWAX serves to reduce this risk by providing a protective barrier.
Tools	Soft cloth. Clean tools with water after use.
	Last undate: 2 May 2023

Last update: 2 May 2023

1 of 2

Stucco Italiano Srl Via Rovereto, 20 - 36030 Costabissara (VI), Italy | Tel +39 0444 700991 | info@stuccoitaliano.it C.F / VAT IT 03744780242 | SDI: M5UXCR1



We have drawn up the material presented above to the best of our technical and experiential knowledge. Nevertheless, our suggestions and recommendations are not guaranteed. All responsibility for the obtained results lies solely with the method and conditions adopted for the application of the product.

TDS PERLA WAX

Last update: 2 May 2023

2 of 2

Stucco Italiano Srl Via Rovereto, 20 - 36030 Costabissara (VI), Italy | Tel +39 0444 700991 | info@stuccoitaliano.it C.F / VAT IT 03744780242 | SDI: M5UXCR1

www.stuccoitaliano.com