

Document type	Technical Data Sheet
Name	PROTECTIVE WAX
Description	Self-Polishing Acrylic Wax protection, it is the ideal protective treatment for REINFORCED MICROCEMENT and MARMORINO VELVET.
Composition	Synthetic wax emulsion dispersed in acrylic base
Versions	Matt, Glossy
Appearance	White milky liquid
Packaging	1 L or 5 L polyethylene packaging
Application	By hand, using a rag or felt wax applicator (wax spreader).
Where to use it	Walls: on finishes such as MARMORINO VELVET, BETON STUCCO Floors: on REINFORCED MICROCEMENT, PASTELLONE, MAGNESITE TERRAZZO
Dilution	Ready to use. It can be diluted 1:3 with water for applications on wall finishes
Consumption	42 ml/sqm of non-diluted product
Drying	1 hour at 20°C to the touch, 48 hours in depth
Application temperatures	min 8 max 35°C – R.U. < 85% ca
VOC Classification	EU Directive 2004/42/CE: EU limit value for this product (cat A/l): 200 g/l (2010). This product contains less than 200 g/l of VOC.
Shelf life	36 months when stored according to the recommended guidelines
Storage	In original sealed packaging between 5° and 35°C in a dry, dark environment
Safety Norms	It is important to adhere to the prevailing safety and hygiene standards while using it. Always keep the product out of reach of children. In the event of ingestion, or allergic reaction seek medical assistance without delay and present the container or label.
Disposal	Product must be disposed of according to norms and regulations in force. Containers must be sent for recycling. Follow directions on the packaging.
Application Instructions	FLOOR APPLICATION Ensure the floors are clean and dry before application. Apply one uniform coat of the desired version of PROTECTIVE WAX (MATT or GLOSSY) using a rag or felt wax applicator (wax spreader). Wait for one hour before applying a second coat in a different direction than the first. It is recommended to apply the wax in thin coats to avoid visible excess wax and prevent damage to the surface. Wait for one to two hours before walking on the surface. PROTECTIVE WAX is self-shining; however, for maximum shine, it is recommended to polish the surface after several hours.
Tools	Rag or felt wax applicator (wax spreader). Clean tools with water after use.

We have drawn up the material presented above to the best of our technical and experiential knowledge. Nevertheless, our suggestions and recommendations are not guaranteed. All responsibility for the obtained results lies solely with the method and conditions adopted for the application of the product.